

LMP 331

Screw-In Transmitter

Stainless Steel Sensor

accuracy according to IEC 61298-2:
standard: 0.35 % FSO
option: 0.25 % / 0.1 % FSO



Nominal pressure

from 0 ... 100 mbar up to 0 ... 40 bar

Output signals

2-wire: 4 ... 20 mA

3-wire: 0 ... 20 mA / 0 ... 10 V

others on request

Special characteristics

- ▶ pressure port G 3/4" flush
- ▶ excellent accuracy
- ▶ small thermal effect
- ▶ excellent long term stability

Optional versions

- ▶ accuracy 0.1% FSO 61298-2
- ▶ IS-version:
Ex ia = intrinsically safe
for gases and dusts
- ▶ SIL 2 application according to
IEC 61508 / IEC 61511
- ▶ different electrical connections
- ▶ customer specific versions
e. g. special pressure ranges
- ▶ drinking water certificate
according to DVGW and KTW

The screw-in transmitter LMP 331 has been designed for continuous level measurement and is characterized by an excellent performance and a robust construction. The modular construction allows the user the highest possible flexibility in the adaption of LMP 331.

Optional features like e.g. an intrinsically safe version or a functionally safe version (SIL 2) increase the advantages when launching and realizing projects for plants and systems.

Preferred areas of use are

-  Plant and machine engineering
-  Energy industry
-  Environmental engineering
(water – sewage – recycling)



Input pressure range																	
Nominal pressure gauge	[bar]	0.10	0.16	0.25	0.40	0.60	1	1.6	2.5	4	6	10	16	25	40		
Level	[mH ₂ O]	1	1.6	2.5	4	6	10	16	25	40	60	100	160	250	400		
Overpressure	[bar]	0.5	1	1	2	5	5	10	10	20	40	40	80	80	105		
Burst pressure ≥	[bar]	1.5	1.5	1.5	3	7.5	7.5	15	15	25	50	50	120	120	210		
Vacuum resistance		p _N ≥ 1 bar: unlimited vacuum resistance									p _N < 1 bar: on request						
Output signal / Supply																	
Standard		2-wire: 4 ... 20 mA / V _S = 8 ... 32 V _{DC}									SIL-version: V _S = 14 ... 28 V _{DC}						
Option IS-version		2-wire: 4 ... 20 mA / V _S = 10 ... 28 V _{DC}									SIL-version: V _S = 14 ... 28 V _{DC}						
Options 3-wire		3-wire: 0 ... 20 mA / V _S = 14 ... 30 V _{DC}									0 ... 10 V / V _S = 14 ... 30 V _{DC}						
Performance																	
Accuracy 1		standard: nominal pressure < 0.4 bar: ≤ ± 0.5 % FSO nominal pressure ≥ 0.4 bar: ≤ ± 0.35 % FSO option 1: nominal pressure ≥ 0.4 bar: ≤ ± 0.25 % FSO option 2: for all nominal pressures: ≤ ± 0.1 % FSO															
Permissible load		current 2-wire: R _{max} = [(V _S - V _{S min}) / 0.02 A] Ω current 3-wire: R _{max} = 240 Ω voltage 3-wire: R _{min} = 10 kΩ															
Influence effects		supply: 0.05 % FSO / 10 V									load: 0.05 % FSO / kΩ						
Long term stability		≤ ± 0.1 % FSO / year at reference conditions															
Response time ²		2-wire: ≤ 10 msec									3-wire: ≤ 3 msec						
¹ accuracy according to IEC 61298-2 – limit point adjustment (non-linearity, hysteresis, repeatability)																	
² with optional accuracy 0,1 % FSO the response time is 200 msec																	
Thermal effects (offset and span)																	
Nominal pressure p _N	[bar]	≤ 0.40									> 0.40						
Tolerance band	[% FSO]	≤ ± 1									≤ ± 0.75						
In compensated range	[°C]	0 ... 70									-20 ... 85						
Permissible temperatures																	
Permissible temperatures		medium: -40 ... 125 °C				electronics / environment: -40 ... 85 °C				storage: -40 ... 100 °C							
Electrical protection																	
Short-circuit protection		permanent															
Reverse polarity protection		no damage, but also no function															
Electromagnetic compatibility		emission and immunity according to EN 61326															
Mechanical stability																	
Vibration		20 g RMS / 10 ... 2000 Hz									according to DIN EN 60068-2-6						
Shock		500 g / 1 msec half sine									according to DIN EN 60068-2-27						
Explosion protection (only for 4 ... 20 mA / 2-wire)																	
Approvals		IBExU 10 ATEX 1068 X / IECEx IBE 12.0027X															
DX19-LMP 331		zone 0: II 1G Ex ia IIC T4 Ga									zone 20: II 1D Ex ia IIIC T135 °C Da						
Safety technical maximum values		U _i = 28 V, I _i = 93 mA, P _i = 660 mW, C _i ≈ 0nF, L _i ≈ 0 μH, the supply connections have an inner capacity of max. 27 nF opposite the housing															
Permissible temperature for medium		in zone 0: -20 ... 60 °C with p _{atm} 0.8 bar up to 1.1 bar in zone 1 or higher: -40/-20 ... 70 °C															
Connecting cables (by factory)		cable capacitance: signal line/shield also signal line / signal line: 160 pF/m cable inductance: signal line /shield also signal line / signal line: 1 μH/m															
Materials																	
Pressure port / housing		stainless steel 1.4404 (316L)															
Option compact field housing		stainless steel 1.4301 (304); cable gland M12x1.5, brass, nickel plated (clamping range 2 ... 8 mm)															
Seals		standard: FKM option: EPDM (without / with drinking water certificate) others on request															
Diaphragm		stainless steel 1.4435 (316L)															
Media wetted parts		pressure port, seals, diaphragm															
Miscellaneous																	
Optionally SIL 2 version ³		according to IEC 61508 / IEC 61511															
Current consumption		signal output current: max. 25 mA									signal output voltage: max. 7 mA						
Weight		approx. 200 g															
Installation position		any ⁴															
Operational life		100 million load cycles															
CE-conformity		EMC Directive: 2014/30/EU															
ATEX Directive		2014/34/EU															
Drinking water certificate ⁵		according to DVGW W 270 and UBA KTW															
³ only for 4...20mA / 2-wire; not in combination with the accuracy 0.1%																	
⁴ Pressure transmitters are calibrated in a vertical position with the pressure connection down. If this position is changed on installation there can be slight deviation in the zero point for pressure ranges p _N ≤ 1 bar																	
⁵ only possible with EPDM seal; not possible with IS-version (explosion protection), with order the indication "with drinking water certificate" is necessary																	

Pin configuration					
Electrical connections	ISO 4400	Binder 723 (5-pin)	M12x1 / metal (4-pin)	compact field housing	cable colours (IEC 60757)
Supply +	1	3	1	IN +	WH (white)
Supply -	2	4	2	IN -	BN (brown)
Signal + (only for 3-wire)	3	1	3	OUT +	GN (green)
Shield	ground pin \oplus	5	4	\oplus	GYNE (green-yellow)
Wiring diagrams					
2-wire-system (current) 			3-wire-system (current / voltage) 		
Electrical connections (dimensions in mm)					
standard 		options 			
ISO 4400 (IP 65)		Binder series 723, 5-pin (IP 67)		M12x1, 4-pin (IP 67)	
cable outlet with PVC cable (IP 67) ⁶		cable outlet, cable with ventilation tube (IP 68) ⁷		compact field housing (IP 67)	
⁶ standard: 2 m PVC cable (without ventilation tube, permissible temperature: -5 ... 70 °C) ⁷ different cable types and lengths available, permissible temperature depends on kind of cable					
Mechanical connection (dimensions in mm)					
standard 			SIL- and SIL-Ex-version 		
G3/4" flush (DIN 3852) with ISO 4400			G3/4" flush (DIN 3852) with ISO 4400		

© 2026 BDI SENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

